


開閉器 GBLS型(扣模器)


SLIDE LOCK(GBLS TYPE)



塑膠模
具用



(Use for 80kg,120kg,150kg)



(Use for 200kg)

Material
M材質
SCM21

扣模器之功能及使用說明:

- 1.本裝置適合於三模板之針點射模，有拉斷料頭與脫模一次完成之功能。(二色成型之最適)
- 2.本產品採用精密鑄造而成，精度高，拉勾採用高級合金鋼經熱處理研磨而成，勾力特強，兩側採用之耐熱彈簧片，彈性佳，耐熱力強，有數十萬次之開模能力。
- 3.本裝置作用力向外側，故不傷模具，裝置時兩邊對稱、固定銷孔用5mm之絞刀絞過後，再以固定銷固定之，以增加固定性。
- 4.本裝置尺寸有二型，但扣模力分為四種，如下：

- GBLS-100拉模力80kg
- GBLS-200拉模力120kg
- GBLS-300拉模力150kg
- GBLS-600拉模力200kg

大型模具使用時可一次安裝2組以上之扣模器

Functions & Instructions:

1. Excellent for 3-pcs mold plates for its precision injection (for example: needle-point injection). It will cut off the excessive materials and leave the mold at the time of finishing. (especially good for double-color injection)
2. Slide Lock was made by precision casting methods.
Hanger was made by heat-treated and grinded alloy steel that provides very strong hanging power. Using heat-resistant springs on the both sides that make the lock slide can endure over 100,000 times of usage.
3. When assemble the Slide lock, line up both sides evenly, then using 5mm reamer to ream.

4. 2 different sizes with 4 different mold clamping force:

- GBLS-100 with mold clamping force up to 100kg
- GBLS-200 with mold clamping force up to 200kg
- GBLS-300 with mold clamping force up to 300kg
- GBLS-600 with mold clamping force up to 600kg

Can be used for more than 2 sets of slide Locks when install into larger molding machines.

Type	Kg	Price 單價
JH065	80	
	120	
	150	
	200	

●Order: Type