



M材質	Inner Hardness	Surface Hardness	Heat Treatment
SKH51	I.H 内部硬度	S.H 表面硬度	热处理
	HRC58°~60°	HRC58°~60°	真空處理 Vacuumed

D	d1	H	Catalog No.		L=100			L=150			L=200	
			Type	d	N=40	N=50	N=70	N=70	N=100			
3	1.5	4.0	JH005	0.5								
				0.6								
				0.7								
				0.8								
				1.0								
4	2.0			0.8								
				0.9								
				1.0								
5	2.5			1.1								
				1.2								
		0.8										
		0.9										
6	3.0	1.0										
		1.1										
		1.2										
		0.8										

● Order: Catalog No. $\square \times \square \times \square \times \square \times \square \times \square$

備注: 1.圖面以外規格可定制。

2.一次單一尺寸訂購100祇以上價格另議。

Remark: 1.Special product is available.

2.Price is negotiable if quantity of each size is more than 100 in one order.

OPTION	CODE	SPEC
	LC	LC=0.1 mm unit L ≤ 40
	LG	LG=0.01 mm unit L ≥ 40
	GVC	S.B=1 mm unit 2 ≤ S ≤ 10, S-5 ≤ B ≤ 30 D ≥ 3
	NP	D ≥ 2.5
	SC	SC=0.005 mm unit D/2 ≤ WC < H/2
	WC	WC=0.005 mm unit D/2 ≤ WC < H/2
	WAC WBC	WAC, WBC=0.005 mm unit D/2 ≤ WAC, WBC < H/2
	RC	RC=0.005 mm unit D/2 ≤ RC < H/2
	TTC	TTC=0.005 mm unit D/2 ≤ TTC < H/2
	STC	STC=0.005 mm unit D/2 ≤ STC < H/2
	HC	HC=0.1 mm unit D+1 ≤ HC < H D ≥ 1.5
	TC	TC=0.1 mm unit T/2 ≤ TC < T D ≥ 1.5